

DecraGroove

Decorative Wood Acoustic Panels



Decrasound has added an exciting range of Timber Ceiling and Wall Panels to its extensive range of decorative interior acoustic products. Called DecraGroove™ these wall & ceiling panels offer a diverse range of perforation patterns and surface finishes to suit any commercial project. The developers of Decragroove have worked with architects and interior designers to release this range of sound absorbing panels, with beautiful, durable laminate and veneer finishes. This gives DecraGroove a unique combination benefits —combining a stylish interior range with excellent sound absorbing properties.

Typical Sound Absorption Values

PANEL PERFORATION	SOUND ABSORPTION AT CENTRE FREQUENCIES (Hertz) SHOWN BELOW:						
	125	250	500	1000	2000	4000	N.R.C.
3mmHOLES @ 8mm	0.37	0.90	1.06	0.90	0.77	0.81	0.90
3mm GROOVES @ 16mm	0.12	0.32	0.68	0.96	0.60	0.68	0.64
6mm SLOTS @ 24mm	0.74	0.76	0.74	0.75	0.60	0.52	0.70

The higher the Sound Absorption figure the better the result. As an example, an NRC (Noise Reduction Co-efficient) of 0.90 equates to up to 90% of the sound striking the panel being absorbed.

For specifying project work it is recommended that an acoustic engineer be consulted.

DecraSorb Acoustic Wall Panels have been tested in approved acoustic laboratories.

Product Composition

- The core material consists superior grade medium density fibreboard (MDF)
- Acoustic absorption is achieved by perforating the panels with repeating patterns of slots, grooves, holes, and custom patterns.
- A range of colours with four types of surface finishes (natural wood, HPL veneer, UV coating, paint or lacquer)
- Tex™ Acoustic Felt is attached to the back of all panels
- Standard panel thickness is 16mm and 18mm
- Class “A” Fire Rating

Applications

DecraGroove *Style'* Ceiling and Wall Panels have been designed for use in most of interior environments to suit the needs of all types of applications. DecraGroove acoustic panels can be tailor made to suit classic or modern designs and be included in projects such as Lecture Theatres, Cinemas, Auditoriums, Churches, Hotels, Theatres, etc. The finished surface of the DecraGroove range is hard wearing and sturdy to withstand environments where physical impact may occur, such as sport complexes, night clubs, and stadiums.


Installation

DecraGroove *'Style'* Timber panels can be installed to ceilings using conventional suspended grid systems. However DecraGroove also has its own unique range of fixings. To fix Wall Panels all is needed is the DecraGroove Flexiline™ system, this enables the panels to be securely fixed while offering the flexibility of easy removal later. Ask your local distributor for details.

Designs or patterns




C.A.P_BB



SB(29/3-32/16)
Venee(Maple)



SB(14/2-16)
Venee(Dark Zebrano)



SB(4/16-10/16)
Emperado Dark



C.A.P_SB



S(13/3)
Venee(Maple)



BB(4/16-10/16)
Botticino



B(6/16)
Veneer(Oak)

Available From

DecraSound Acoustic Products

Head Office

**Init 4, 99-101 Western Avenue,
Westmeadows Victoria Australia 3049**

Web: www.decrasound.com.au

Email: sales@decrasound.com.au

Distributed by: