



Just Sounds Better

Decragroove

Decorative Grooved Acoustic Wood Panels



Decra Acoustics has added an exciting range of Timber Ceiling and Wall Panels to its extensive range of decorative interior acoustic products. Called DecraGroove™ these wall & ceiling panels offer a diverse range of perforation patterns and surface finishes to suit any commercial project. The developers of DecraGroove have worked with architects and interior designers to release this range of sound absorbing panels, with beautiful, durable laminate and veneer finishes. This gives DecraGroove a unique combination of benefits – combining a stylish interior range with excellent sound absorbing properties.

Typical Sound Absorption Values

SOUND ABSORPTION AT CENTRE FREQUENCIES (Hertz) SHOWN BELOW:							
PANEL PERFORATION	125	250	500	1000	2000	4000	N.R.C.
3mmHOLES @ 8mm	0.37	0.90	1.06	0.90	0.77	0.81	0.90
3mm GROOVES @ 16mm	0.12	0.32	0.68	0.96	0.60	0.68	0.64
6mm SLOTS @ 24mm	0.74	0.76	0.74	0.75	0.60	0.52	0.70

The higher the Sound Absorption figure the better the performance. As an example, an NRC [Noise Reduction Co-efficient] of 0.90 equates to up to 90% of the sound striking the panel being absorbed. For specifying project work, it is recommended that an acoustic engineer be consulted. DecraGroove Acoustic Panels have been tested in approved acoustic laboratories.

Product Composition

- The core material consists of superior grade medium density fibreboard [MDF]
- Acoustic absorption is achieved by perforating the panels with repeating patterns of slots, grooves, holes, or custom patterns, and installing acoustic insulation behind the panels.
- A range of colours with four types of surface finishes [natural wood, HPL veneer, UV coating, paint or lacquer]
- Tex™ Acoustic Felt is attached to the back of all panels
- Standard panel thickness is 16mm and 18mm
- Class “A” Fire Rating


Applications

DecraGroove Ceiling and Wall Panels have been designed for use in interior environments, to suit the needs of all types of applications. DecraGroove acoustic panels can be tailor made to suit classic or contemporary interior designs, and be included in projects such as Lecture Theatres, Cinemas, Auditoriums, Churches, Hotels, Theatres, etc. The finished surfaces of the DecraGroove range are hard wearing and sturdy to withstand environments where physical impact may occur, such as sport complexes, night clubs, and stadiums.


Installation

DecraGroove acoustic panels can be installed to ceilings using conventional suspended grid systems. However, DecraGroove also has its own unique range of fixings. To fix Wall Panels DecraGroove Flexiline™ system is available. This system enables the panels to be securely fixed while offering the flexibility of easy removal later. Ask your local distributor for details.


Designs or patterns




DG T8



DG T16



DG T32



DG T48

Sizes

2400mm*1197mm, 2400mm*581mm,
2400mm*197mm, 2400*293mm.
1200mm*1197mm
1200mm*581mm

Thicknesses

12mm,16mm,18mm

Facings

Decorative Laminae
High Pressure Laminate
Painted
Real Wood Veneers

Available From

Decra Acoustic Products USA
Suite 112 101 North Tryon Street
Charlotte, NC 28246

Web: www.decra-acoustic.com

p: 980-434-2174 mail: sales@decra-acoustic.com